

Flat LED downlights

These ultra slim downlights are ideal for surface mounting under wall cabinets and are supplied with all fixings, screws and self adhesive pad included.



Can also be recess mounted for completely flush fitting.



4 Lighting

Flat LED downlight, 12V/1.2W

- Slim design, ideal for surface mounting under wall cabinets or can be recess mounted
- Screw fixing, fixings and self adhesive pad included
- LED grid contains 19 diodes
- Colour temperature: 5,000 K
- Light output: Lm per Watt: See table below
- Voltage: 12V. Wattage 1.2W
- With 2.5 m lead with connector
- Thermoplastic, satin chrome finish
- **Order driver separately for single lights, shown below, Cat. No. 830.69.790**



Single light only (order driver Cat. No. 830.69.790 separately)			
LED colour	Cool white	Warm white	Blue
Light output	25 Lm/Watt	18 Lm/Watt	7.5 Lm/Watt
Cat. No.	830.68.750	830.68.751	830.68.850

Order qty: 1 pc

Packed set			
LED colour	Cool white	Warm white	Blue
Light output	25 Lm/Watt	18 Lm/Watt	7.5 Lm/Watt
3 lights with driver	830.68.763	830.68.762	830.68.863
5 lights with driver	830.68.765	830.68.764	830.68.865

Order qty: 1 set



LED driver, 240V

- For indoor use only
- For use with flat LED down light shown left
- Driver height x width x depth: 20 x 120 x 45 mm
- 240V white plastic driver with 1.5 m bare ended mains lead and white plastic distributor
- Maximum 6 lights per transformer
- Mains plug not included - must be fitted by a qualified electrician



Driver 240V/12V	Cat. No.
15W with 6-way distributor	830.69.790

Order qty: 1 pc

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.