



A Drilling jig

- For mounting Dialock DTSH door terminals on wooden doors
- **Using the drilling jig:**
Align drilling jig with stop parallel to door edge and fix with suitable screw clamp
Drill required holes into door using the drilling jig (at a right angle to door panel)
Do not drill through the door panel - use drilling jig on both sides
- **Drilling dimensions:**
3 x Ø 18 mm continuous
1 x Ø 16 mm continuous
1 x Ø 8 mm drilling for cable up to lock recess (only with logging of emergency opening)
1 x Ø 25 mm routing on the outside, min. 7 mm deep
- 1 x Ø 32 mm additional routing on the outside up to lock recess (only with logging of emergency opening)

Cat. No. 917.90.005

Order qty: 1 pc



B Twist drill bit, Ø 8 mm

- For drilling holes for screws through doors
- High speed steel (HSS)

Cat. No. 001.41.248

Order qty: 1 pc

C Drill bit, Ø 16 mm

- For drilling through-hole for leading cables through wooden doors

Cat. No. 910.54.994

Order qty: 1 pc

D Router bit, Ø 25 mm

- For through-hole to lock nut on wooden doors
- With reducing sleeve and centering pin

Cat. No. 910.54.995

Order qty: 1 pc

E Router bit, Ø 32 mm

- For widening the cable drilling on the outside through to the lock recess (only when logging the emergency opening)
- With centering pin

Cat. No. 910.54.997

Order qty: 1 pc

F Spacer

- For use with thinner door panels
- Dimensions: 226 x 65 x 3 mm
- Not for use on fire resistant and smoke control doors
- Black ABS plastic

Cat. No. 917.90.492

Order qty: 1 pc



G Fixing materials

- Comprises:
1x 8 mm lever handle spindle
4x M4 threaded screws
- Yellow galvanized steel spindle and galvanized steel screws

For door panel thickness	Spindle length	Thread length of screw	Cat. No.
37-47 mm	100 mm	50 mm	917.90.410
47-57 mm	110 mm	60 mm	917.90.411

Order qty: 1 set

H Fitting set

- Comprises of:
2x Cylinder spindle
2x Adhesive labels
1x Retaining ring
2x Threaded spindles for handles
1x Wood screw Ø 3 x 14 mm
1x Break seal profile cylinder cover

Cat. No. 917.90.258

Order qty: 1 set



I Batteries

- Alkaline manganese, 1.5 Volt type E91 (AA)
- 4 pcs required per DTSH door terminal

Cat. No. 910.54.980

Order qty: Multiples of 4 pcs



J Pliers for retaining ring

- To unclip retaining ring
- For fitting lever handle spindle, as required

Cat. No. 917.90.900

Order qty: 1 pc