


Intumescent strip, plain

- Generally for half hour (FD30 rating) or one hour (FD60 rating) fire doors
- Self adhesive fixing
- Certifire approved, certificate No. CF276
- Passed as BS 476 part 22 and 31.1
- LANTAC Building Control Approved
- NHBC Type Approved

FD30 rating			
Length	Size	White	Brown
1050 mm	10 x 4 mm	950.18.057	950.18.051
2100 mm	10 x 4 mm	950.18.007	950.18.001
1050 mm	15 x 4 mm	950.18.067	950.18.061
2100 mm	15 x 4 mm	950.18.017	950.18.011
FD60 rating			
2100 mm	20 x 4 mm	950.18.027	950.18.021
2100 mm	25 x 4 mm	950.18.037	950.18.031

Order qty: 1 pc



Intumescent strip, with brush seal

- Generally for half hour (FD30 rating) or one hour (FD60 rating) fire doors
- Self adhesive fixing
- Certifire approved, certificate No. CF276
- Smoke seals to EN 1634-3
- Passed as BS 476 part 22 and 31.1
- LANTAC Building Control Approved
- NHBC Type Approved

FD30 rating			
Length	Size	White	Brown
1050 mm	10 x 4 mm	950.18.157	950.18.151
2100 mm	10 x 4 mm	950.18.107	950.18.101
1050 mm	15 x 4 mm	950.18.167	950.18.161
2100 mm	15 x 4 mm	950.18.117	950.18.111
FD60 rating			
2100 mm	20 x 4 mm	950.18.127	950.18.121

Order qty: 1 pc



Door closer, lock and hinges are not included

Ironmongery protection pack

- Tested to BS 476, up to 60 min fire rating
- Easy to install
- Maintenance free
- LANTAC Building Control Approved
- NHBC Type Approved
- Graphite based intumescent material
- **Fire door pack consists of:**
 3x 36 x 300 x 2 mm hinge strips
 1x 500 x 500 x 0.8 mm lock and closer protection
- **Hinge pack consists of:**
 6x 36 x 300 x 2 mm strips
- **Lock/door closer pack - lock sheet**
 1x 500 x 500 x 0.8 mm pad
- **Lock/door closer pack - self adhesive**
 1x 500 x 500 x 0.8 mm pad

Type	Cat. No.
Fire door pack	950.18.900
Hinge pack	950.18.912
Lock/door closer pack - lock sheet	950.18.920
Lock/door closer pack	950.18.921

Order qty: 1 pc