



**Espagnolette bolt**

- Offset gearbox position
- 20 or 25 mm backset
- 8 mm height of security stud
- Complies with BS 1449
- Mushroom rollers/locking points comply with BS 970 040 A04
- Adjustable rollers
- Gear box components die cast for precision and strength to BS 1004A
- 90° handle rotation gives 20 mm linear movement of rail/locking elements
- Pinion gear accepts standard 7 mm AF drive spindle
- Free running roller locking elements for ease of action and reduced wear
- Independent neutral salt corrosion test passed to 72 hours exposure
- Case drilled and tapped M5
- Silver nickel
- Order keeps separately, see below

Backset 20 mm, case size 28 mm		
Length	No. of locking points	Cat. No.
250 mm	2	970.11.625
400 mm	2	970.11.640
600 mm	2	970.11.660
800 mm	3	970.11.680
1000 mm	3	970.11.700
1200 mm	4	970.11.720
Backset 25 mm, case size 33 mm		
Length	No. of locking points	Cat. No.
400 mm	2	970.11.840
600 mm	2	970.11.860
800 mm	3	970.11.880
1000 mm	3	970.11.900
1200 mm	4	970.11.920

Order qty: 1 pc




**Night vent security keep**

- Order one per mushroom bolt
- Surface fixed
- Durapress steel

Cat. No.	
Night vent keep	970.11.105

Order qty: 1 pc





**Night vent security keep, narrow**

- Order one per mushroom keep
- Surface fixed
- Durapress steel

Cat. No.	
Night vent narrow keep	970.11.115

Order qty: 1 pc



**Machine screws, countersunk head**

- Pozidrive slot
- Zinc plated steel

Ø x length	Cat. No.	Order qty
M5 x 40 mm	020.08.068	250 pcs
M5 x 50 mm	020.08.070	100 pcs

Order qty: See table above