


LOOX 12V LED 2020 DOWNLIGHT



This light is suitable for use in wet areas (zone 1) of bathrooms or kitchens when recess mounted. It also has an opaque cover which provides an even distribution of light.



Loox 12V LED 2020 downlight, Ø 65 mm, IP44 rated



IP44

- > For recess mounting, press-fit in Ø 55 mm hole
- > Voltage: 12V. Wattage: 3.2W
- > With 2.0 m lead with Loox 12V connector
- > Zinc alloy housing with opaque lamp cover
- > Order qty: 1 pc

	3000 K	4000 K	6000 K
Output:	3000 K	4000 K	6000 K
Light colour:	Warm white	Cool white	Daylight white
Number of diodes:	6	6	6
Light output (Lm):	122	107	99
Wattage (W):	3.2	3.2	3.2
Efficacy (Lm/W):	38	33	31
Colour Rendering Index:	84	84	84

Distance	110°	3000 K	4000 K	6000 K
250 mm		510 Lx	550 Lx	550 Lx
500 mm		173 Lx	182 Lx	182 Lx
750 mm		83 Lx	90 Lx	90 Lx
1000 mm		46 Lx	46 Lx	46 Lx




> Order bezel separately for surface mounting



Finish	3000 K	4000 K	6000 K
Matt nickel	833.72.020	833.72.021	833.72.022
Polished chrome	833.72.030	833.72.031	833.72.032

Loox 12V LED 2020 bezel, Ø 66.5 mm



> Note: IP rating is 20 when light is surface mounted



- > For surface mounting Loox LED 2020 downlight
- > Screw fixing, fixings included
- > Zinc alloy
- > Order qty: 1 pc



Finish	Cat. No.
Nickel silver coloured	833.72.800
Polished chrome	833.72.802



- > Order Loox 12V driver and mains lead separately, shown on page 62
- > Order switch separately, switches shown on pages 134-136