


SYMO 3000 CYLINDER CORES WITH PIN TUMBLERS

Symo 3000 cylinder cores can be installed, repositioned or replaced quickly without tools, simply by using the removal key


8

Cabinet Locks, Catches and Bolts: Locks

Inserting the cylinder core




Remove protective cap from cylinder housing




Insert the cylinder core into the cylinder housing and exert light pressure until cylinder core snaps into place

Removing the cylinder core




The cylinder core can only be removed from the cylinder housing by using the removal key (removal key can only be used in unlocked position)



Insert the removal key into the cylinder housing and withdraw under slight pressure

Cylinder core



- > Cylinder core for left or right hand use
- > 6 pairs of pin tumblers = 10,000 possible key changes
- > Nickel-plated zinc alloy housing, brass pin tumblers
- > Accessories: 1x key
- > Order qty: 1 pc

| Key type | Cat. No. |
|--------------------------------|------------|
| Random key change | 210.45.600 |
| Keyed alike: Key change | |
| 001 A | 210.45.601 |
| 002 A | 210.45.602 |
| 003 A | 210.45.603 |
| 004 A | 210.45.604 |
| 005 A | 210.45.605 |
| 006 A | 210.45.606 |
| 007 A | 210.45.607 |
| 008 A | 210.45.608 |
| 009 A | 210.45.609 |
| 010 A | 210.45.610 |
| Removal key | 210.45.090 |

Additional or replacement key



- > When ordering please specify key numbers
- > Steel
- > Order qty: 1 pc



| Finish | Cat. No. |
|------------|------------|
| New silver | 210.45.000 |



A guide to master key and general master key systems is shown on page 7

! For master and general master key systems:
If the master key/general master key cylinder cores are opened or locked with the master key/general master keys, they must also be re-locked or re-opened with the same key in order to restore the single key function which will otherwise be lost

'Standard' master key (MK) system

- > Order keys separately
- > Key numbers MS A001-300
- > Nickel-plated zinc alloy cylinder core housing, new silver key
- > Order qty: 1 pc



| Item | Cat. No. |
|---------------|------------|
| Cylinder core | 210.45.697 |
| Key | 210.45.010 |
| Master key | 210.45.011 |
| Removal key | 210.45.090 |

Master key (MK) system, as required

- > Order keys separately
- > Nickel-plated zinc alloy cylinder core housing, new silver key
- > Order qty: 1 pc

| Item | Cat. No. |
|---------------|------------|
| Cylinder core | 210.45.698 |
| Key | 210.45.020 |
| Master key | 210.45.021 |
| Removal key | 210.45.093 |

General master key (GMK) system, as required

- > Order keys separately
- > Nickel-plated zinc alloy cylinder housing, new silver key
- > Order qty: 1 pc

| Item | Cat. No. |
|--------------------|------------|
| Cylinder core | 210.45.699 |
| Key | 210.45.020 |
| Master key | 210.45.021 |
| General master key | 210.45.022 |
| Removal key | 210.45.093 |

TOH TECHNOLOGY 2018, © Hafele U.K., Ltd 2018. Dimensional data not binding. We reserve the right to alter specifications without notice.